

COLOR TUNABLE DOWN LIGHT | 2700K ~ 6500K

VILD 2107 / 2113 (Fixed/Adjustable)



Round recessed LED CCT darklighter downlight, LED color tunable from warm white 2700K to neutral white 4000K to daylight 6500K. Aluminum round white trim. For indoor use.

VILD 2113 CCT **LED Power: 15W**

XXX lm (luminaire output)
Cutting hole: Ø100mm
Dimension: Ø133 x H91.5mm

VILD 2107 CCT **LED Power: 15W**

XXX lm (luminaire output)
Cutting hole: Ø75mm
Dimension: Ø87 x H118.5mm


LED Driver:
Remote, 0-10V CCT Dimming Driver, 25-42VDC, 350mA (MAX. 14.7W)

COLOR TUNABLE DOWN LIGHT | 2700K ~ 6000K


VFDC-398R (Fixed/Adjustable/Wall Washer)




VFDC398R-F
(Fixed)



VFDC398R-AD
(Adjustable)



VFDC398R-WW
(Wall Washer)



LED Power : 12w COB
Luminous Flux : 1200 lm
 Dimension : Ø85xH100 mm
 Cutting Hole : Ø75 mm



LED Power : 18w COB
Luminous Flux : 1800 lm
 Dimension : Ø115xH130 mm
 Cutting Hole : Ø105 mm



LED Power : 24w COB
Luminous Flux : 2400 lm
 Dimension : Ø115xH130 mm
 Cutting Hole : Ø105 mm



LED Power : 35w COB
Luminous Flux : 3500 lm
 Dimension : Ø142xH175 mm
 Cutting Hole : Ø125 mm



External LED Driver

- Trim : Die-cast aluminium
- Body : Die-cast aluminium
- Housing : 1.2mm matt black paint
- Optic : High efficiency reflector
- *Trimless version available

Ordering Code: VFDC-398R - T - XXW - YYD - ZZZ - AA

Example: **VFDC-398R-AD-18W-24D-930-ND** (for Trimless version add suffix "TRL")

T = F for Fixed, **AD** for Adjustable, **WW** for Wall Washer

XX = (Watt) e.g. 12w, 18w, 24w, 35w

YY = Beam angle in degrees.

ZZZ = the code for color rendering and color temperature, eg. **927** = CRI >90 and CCT - 2700K; **930** = CRI >90 and CCT - 3000K; **940** = CRI >90 and CCT - 4000K.

AA is the dimming requirements = **ND** for non dim, **DA** for DALI, **AN** for 0-10V, **TR** for Trailing edge dimming

SWITCHING COLOR SELECTABLE DOWN LIGHT

VSIG-LDE-XX-CCT

IP20

CRI 80



Round recessed LED CCT luminaire with frosted acrylic diffuser. LED color selectable from warm white 3000K to neutral white 4000K to daylight 6500K by on/off wall switch. Aluminum round white trim. For indoor use.

LED Power: 12W

Selectable Color: 3000K - 4000K - 6500K

1200 lm (luminaire output)

Cutting hole: Ø150mm

Dimension: Ø165 x H50mm

LED Power: 18W

Selectable Color: 3000K - 4000K - 6500K

1800 lm (luminaire output)

Cutting hole: Ø200mm


Dimension: Ø215 x H50mm

LED Driver: Built-in, non-dimmable


12W, 3000K

18W, 3000K

Luminous Intensity Distribution Curve(cd/klm)



Luminous Intensity Distribution Curve(cd/klm)



Ordering Code: VSIG - LDE - XXW - CCT

Example: **VFSIG-LDE-18W-CCT**

XX = (Watt) e.g. 12w, 18w,