



**COB ANTI-GLARE DOWN LIGHT** | Round | Recessed

**VFDC-202R**

IP20 |   | **CRI 80** **CRI 85**




**Color Option**



- White (standard)
- Gray
- Black

**Beam Angle**



**Suitable LED Chip: Citizen, Bridgelux, CREE COB.**




CITIZEN





BRIDGELUX





CREE


**10W, COB**   
 220-240V, 50/60Hz  
 3000K  
**800 lm (luminaire output)**  
 - Non-dimmable





**15W, COB**   
 220-240V, 50/60Hz  
 3000K  
**1200 lm (luminaire output)**  
 - Non-dimmable



**20W, COB**   
 220-240V, 50/60Hz  
 3000K  
**1600 lm (luminaire output)**  
 - Non-dimmable



**25W, COB**   
 220-240V, 50/60Hz  
 3000K  
**2000 lm (luminaire output)**  
 - Non-dimmable



**Ordering Code: VFDC-202R - XXW - ZZZ**

Example: VFDC-202R-15W-830

**XX** = (Watt) e.g. 10W, 16W, 30W, 40W

**ZZZ** = the code for color rendering and color temperature, eg. **827** = CRI >80 and CCT - 2700K; **830** = CRI >80 and CCT - 3000K; **840** = CRI >80 and CCT - 4000K