


COB ANTI-GLARE DOWN LIGHT | Round | Recessed

VFDC-368R


IP20




CRI 80 **CRI 85**




10W 60°




20W 60°




25W 60°



30W 60°



50W 60°



5W COB

2700K-6500K
 800 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: Ø80mm
 Dimension: Ø95 x H55mm



10W COB

2700K-6500K
 1500 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: Ø80mm
 Dimension: Ø95 x H75mm



10W COB

2700K-6500K
 2000 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: Ø100mm
 Dimension: Ø115 x H90mm



20W COB

2700K-6500K
 2500 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: Ø140mm
 Dimension: Ø160 x H95mm



30W COB

2700K-6500K
 3000 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: Ø200mm
 Dimension: Ø215 x H130mm



50W COB

2700K-6500K
 5000 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: Ø200mm
 Dimension: Ø215 x H145mm



Where **VV (Reflector)** = 01 or 02 or 03



01-Matt White



02-Silver



03-Chrome

Ordering Code: VFDS-368R- XXW - ZZZ - VV

Example: VFDS-368R-20W-830-03

VV = (Reflector) **01, 02 or 03**

XX = (Watt) e.g. 7W, 10W, 15W...

ZZZ = the code for color rendering and color temperature, eg.
827 = CRI >80 and CCT - 2700K; **830** = CRI >80 and CCT - 3000K; **840** = CRI >80 and CCT - 4000K

COB ANTI-GLARE DOWN LIGHT | Square | Recessed


VFDC-368S

IP20




CRI 80


CRI 85




15W 60°




20W 60°



30W 60°



50W 60°



6W SAMSUNG

2700K-6500K
 720 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: 80 x 80mm
 Dimension: 90 x 90 x H40mm




12W SAMSUNG

2700K-6500K
 1440 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: 110 x 110mm
 Dimension: 125 x 125 x H53mm



18W SAMSUNG

2700K-6500K
 2160 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: 145 x 145mm
 Dimension: 160 x 160 x H53mm



24W SAMSUNG

2700K-6500K
 2880 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: 175 x 175mm
 Dimension: 190 x 190 x H53mm



36W SAMSUNG

2700K-6500K
 4320 lm (luminaire output)
 180-240V, 50/60Hz
 Cutting hole: 200 x 200mm
 Dimension: 215 x 215 x H60mm



Where **VV= 01 or 02 or 03**



01



02



03

Ordering Code: VFDC-368S - VV - COB - XXW - ZZZ

Example: VFDC-368S-03-COB-50W-830

VV = 01/02/03

XX = (Watt) e.g. 12W, 15W, 20W...

ZZZ = the code for color rendering and color temperature, eg. 827 = CRI >80 and CCT - 2700K; 830 = CRI >80 and CCT - 3000K; 840 = CRI >80 and CCT - 4000K