

HIGH EFFICIENCY PROFESSIONAL SERIES | Square | Recessed

VDIL-HX

IP44





CRI 80



Color: White
Material: Die-cast Aluminium+Plastic+PMMA



DA606S-M12

Samsung SMD
12W, 300mA, 40V
3000K/4000K/5000K
1000 lm (luminaire output)
Cutting hole: 140 x 140mm
Dimension: 160 x 160 x H85mm





DA607S-M20

Samsung SMD
18W, 600mA, 30V
3000K/4000K/5000K
1500 lm (luminaire output)
Cutting hole: 186 x 186mm
Dimension: 200 x 200 x H97mm





DA608S-M30

Samsung SMD
25W, 600mA, 42V
3000K/4000K/5000K
2200 lm (luminaire output)
Cutting hole: 202 x 202mm
Dimension: 220 x 220 x H108mm



DA609S-M36

Samsung SMD
34W, 900mA, 38V
3000K/4000K/5000K
3100 lm (luminaire output)
Cutting hole: 282 x 282mm
Dimension: 300 x 300 x H125mm



Ordering Code: VDIL-HX - V - XXW - ZZZ

Example: **VDIL-HX-DA606S-M12-12W-840**

V = DA606R-M16; DA607-M20; DA608R-M24

XX = (Watt) e.g. 14W, 18W, 20W...

ZZZ = the code for color rendering and color temperature, eg. **827** = CRI >80 and CCT - 2700K; **830** = CRI >80 and CCT - 3000K; **840** = CRI >80 and CCT - 4000K