



LED SpotRF 2W EcoMax

Features

- Flicker free
- Integrated clip mounts
- Compact size

Benefits

- Stress free ambient light
- Easy installation
- Use in tight spaces, minimal aesthetic footprint

Application



Specification

Item Code	Item Description	Power (W)	Power Factor	Lumen (lm)	Efficacy (lm/W)	Input Current (mA)	CRI	CCT (K)	Lifetime (L70B50)
140047271	LEDspotRF-E 2W-3000-25D-AL-GP	2	0.40	80	40	22	≥80	3000	20Khrs
140047272	LEDspotRF-E 2W-4000-25D-AL-GP	2	0.40	80	40	22	≥80	4000	20Khrs
140047273	LEDspotRF-E 2W-6500-25D-AL-GP	2	0.40	80	40	22	≥80	6500	20Khrs

Technical Specifications	
On / Off Cycles	20,000
Colour Consistency (SDCM)	7
Dimmable	No
Beam Angle (°)	25
Finishing Colour	Silver
IP	20
Driver Integrated (Yes/No)	No
Glow Wire Test	650°C
Driver Failure Rate	1% at 5000h
Weight (kg/pc)	0.03


Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Mechanical Properties	
Housing Material	Aluminum
Optical Material	PMMA



Application Conditions	
Operating Temperature	-10-40°C
Application Temperature	25°C
Storage Environment	-25-50°C



Dimensional Drawing



Photometric Data



2W

Cut-out Drawing



Ø30
2W